

Guardex



SF-8065

X-RAY BAGGAGE SCANNER

Operating Environment :

- * Storage Temperature; -20oC to 60oC
- * Operating Temperature; 0oC to 45oC
- * Relative Humidity; 20 to 95% non-condensing
- * System Power; 220 VAC (±10%) 50±3HZ
- * Power wastage; 1.0 KW (Max)
- * Noise < 55DB

bilmak security systems

T : 0 212. 225 80 50 pbx
M : bilmak@bilmak.com.tr
www.bilmak.com.tr



Guardex

SF-8065

X-RAY BAGGAGE SCANNER

General Specifications:

Tunnel Size : 800(W)×650(H)mm

Conveyor Speed: 0.22m/s

Conveyor Max Load: 200 kg

Single inspection dosage:

< 1.15μGy

Leakage radiation: <0.14μGy/h

Wire Resolution: 40AWG

Steel Penetration: 38mm

Film Safety: For ISO 1600



X-RAY GENERATOR

Orientation: Downward

Tube Current:0.4~0.7MA(adjustable)

Anode Voltage:100~160KV(adjustable)

Angle: 80°

Generator cooling/working periods: Sealed oil bath with forced air/100%

X-RAY Sensor:

L-shaped array detector, 24bit