



H.264 DVR

CS-D6516RA



■ Features

16CH DIGITAL VIDEO RECORDERS

- Support Analog/AHD/CVI/TVI 2.0/TVI 3.0/Network
- Input:16CH BNC / 8CH IP
- Support Human Detection
- Support H.265/H.265+/H.264/H.264+ Video Compression
- 2 SATA Hard Disk (2.5"/3.5"SATA, Up to 16TB)
- Support a variety of Language

System

Main Processor MC6650

Operating System Embedded LINUX

Video

Input Analog : 16*(TVI/AHD: 5M@12fps; AHD/TVI/CVI: 4M@15fps;AHD/TVI/CVI: 1080P/720P; Analog: 960H)
Analog+Network: 2*Analog(5MP)+14*network(MAX 8MP),4*Analog(5MP)+12*network(MAX 8MP),6*Analog(5MP)+10*network(MAX 8MP),8*Analog(5MP)+8*network(MAX 8MP),10*Analog(5MP)+6*network(MAX 8MP),12*Analog(5MP)+4*network(MAX 8MP),14*Analog(5MP)+2*network(MAX 8MP)
Network: 16*8MP/5MP/4MP/3MP/1080P/960P/720P(Total incoming bandwidth ≤80M)

Input 16CH BNC

Signal Type Analog/AHD/CVI/TVI 2.0/TVI 3.0/Network

Audio

Input	6 Channel RCA, support AOC
-------	----------------------------

Two-way Audio	NO
---------------	----

Output	1 Channel RCA
--------	---------------

Alarm

Sensor Input	4
--------------	---

Output	1
--------	---

Motion Detection	16 Channel
------------------	------------

Trigger Events	Recording, Email, Screen tips, Buzzer, Push notifications(motion detection)
----------------	---

Email Alarm	Send Image to The Designated E-mail
-------------	-------------------------------------

AI Function

Human Detection	YES
-----------------	-----

PTZ

Interface	RS485
-----------	-------

Protocol	Pelco-D, Pelco-P
----------	------------------

Baud Rate	110~921600
-----------	------------

Address	0~255
---------	-------

Display

VGA	Resolution:1920 × 1080P, 1280 × 1024 , 1280 × 720,1024 × 768
-----	--

HD Output	Resolution:1920 × 1080P, 1280 × 1024 , 1280 × 720,1024 × 768
-----------	--

Display Split	1/4/8/9/16
---------------	------------

Privacy Masking	3 Rectangular Zones (Each camera)
-----------------	-----------------------------------

OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording
-----	--

Recording

Video Compression	H.265/H.265+/H.264/H.264+
Audio Compression	G.711U/G.711A
Resolution	5MP_Lite(1280×1952),4MP_Lite(1280×1440),1080N(960×1080),720P(1280×720),960H(960×480)
Video Quality	Lowest/Low/Ordinary/Good/Better/Best
Record Rate	Analog: PAL: 5MP_Lite(1280×1952 16*6fps),4MP_Lite(1280×1440 16*8fps),1080N(960×1080 16*15fps),720P(1280×720 16*15fps), 960H(960×480 16*25fps) NTSC:5MP_Lite(1280×1952 16*6fps),4MP_Lite(1280×1440 16*8fps),1080N(960×1080 16*15fps),720P(1280×720 16*15fps), 960H(960×480 16*30fps) Pure IP(H.265): PAL :8MP@9x25fps, 5MP@12x25fps,4MP@16x25fps, 3MP@16x25fps, 1080P@16x25fps, 960P@16x25fps, 720P@16x25fps, D1@16x25fps NTSC:8MP@9x30fp, 5MP@12x30fps,4MP@16x30fps, 3MP@16x30fps, 1080P@16x30fps, 960P@16x30fps, 720P@16x30fps, D1@16x30fps
Record Mode	Manual Timer Motion Detection Alarm

Playback & Backup

Decode Capability	4*1080P@30fps
Sync Playback	Pure Analog: 16CH 5M_LITE@6fps, 15CH 4M_LITE@8fps,16CH 1080N@15fps, 16CH 720P@15fps,16CH 960H@30fps Mix Mode: 1CH 4K@30fps,1CH 5M@30fps, 2CH 4M@30fps,2CH 3M@30fps, 4CH 1080P@30fps, 4CH 720P@30fps,4CH 5M_LITE@6fps, 4CH 4M_LITE@8fps,4CH 1080N@15fps, 4CH 720P@15fps,4CH 960H@30fps Pure IPC: 1CH 4K@30fps,1CH 5M@30fps, 2CH 4M@30fps,2CH 3M@30fps, 4CH 1080P@30fps,4CH 720P@30fps,4CH D1@30fps
Remote Playback	4 Channel / 1Channel
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection,Alarm,Tag
Playback Functions	Play, Pause, Stop, Fast play, Slow play, Rewind, Single frame forward/back, Digital Zoom, Full screen
Smart Phone Playback	4 Channel
Backup Mode	USB Device(with format FAT 32)/Network/FTP

Network

Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP,DHCP, FTP, DDNS, RTP, RTSP, RTCP

Hard Disk Driver

Interface Type	2 SATA Interface
Capacity	2 SATA Hard Disk (2.5"/3.5" SATA, Up to 16TB)

General

Language	Simplified Chinese,Traditional Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Japanese,German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek, Vietnamese,
UTC Control	YES
USB Interface	2 USB 2.0 Interfaces
Power consumption	DC 12V/4A ≤15W (Without Hard Disk)
Working Environment	-10~55°C/10~90%
Dimension (W×D×H)	310*295*46(mm)
Weight	4kg (Without HDD)