



Features

- Work distance under typical conditions:40m(120 ft).
- Note:The actual distance depends on RF signal reception,reflection,and interference.
- Audio Frequency Response (+/-3dB) 80Hz 16KHz.
- Total harmonic distortion(+/-30KHz deviation,1KHz audio)<1%.
- Dynamic range:>A-weighted 90 db.
- Operating temperature range:-10℃to+50℃.
- NOTE:Battery characteristics may affect this range.
- Wireless Conference Microphone.
- Max Audio Input Level:0dBV.
- Size:85mm height X 23mm wide X65 mm thick.
- Weight:85g(without battery).
- Power Requirements:2"AA"size alkaline or rechargeable batteries.
- Battery Life:>8hours(alkaline).
- Receiver Audio output frequency(reference+/-30KHz,1KHz).
- XLR connector(into 600 ohm load):-12dBV.
- 1/4 inch connector(into 3000 ohm load):-18dBV.
- Output Impedance:XLR connector:200 ohms.
- 1/4 inch connector:1 kilohms.
- Sensitivity:(demodulator output signal to noise ratio is 30dB) <-92dBm.
- Image Rejection:>80dB.
- Size:44 mm height X212 mm wideX280 mm thick.
- Weight:3500g.
- Power requirements:220V DC from external power supply.