

## GRD-FH990

### Specification

Single Lane Dimension: 1700\*1460\*2300 mm

Double lane Dimension: 2400\*1460\*2300 mm

Rod material: 304 stainless steel

Thickness : 1.5 mm

Lane width : ≤550 mm

speed: 35 person/min adjustable

Power supply voltage: AC 85 - 230 V

Working voltage: DC 24 V

Working temperature: -20°C to 60°C



## FULL HEIGHT SINGLE LANE TURNSTILE GATE

### Functions

Adopt High-level full-automatic intelligent mechanism ,Brushless DC motor, System operation stable with low noise,

Anti-pinch and anti-collision function, Automatical control system ,Power board, Passage LED indicator , Passage Mode setting

Anti-shock function, the swing arm is automatically locked when no open signal is received;

The power-off the flap is automatically opened and automatically closed when it is powered, which meets the fire protection requirements.

with time protection and automatical reset function

Unified electrical interface ,Can be connected with reading and writing equipments.

### Our Advantages

Experience factory , all size ,thickness and appearance can be customized . OEM & ODM requirements are accepted

Can be connected with Access control systems , Security Checking system . And be able to provide system integration solutions.

Strict production process and quality control, assure of our products quality .

Professional sales team and after services team , can offer local services, looking for long term cooperation with you .